

ENGINE DRIVEN WELDER MS 200 S



- DC welder
- One man carry (28 kg)
- Two - stroke engine
- Auto Idle
- Includes welding cables

Standard equipment 	Gasoline engine	Air cooling	Manual recoil	Welding cables						
	Generator high frequency									

Options on request ● Inductance to improve welding performance RL1

Technical data MS 200 S

D.C. WELDING	High frequency, self-excited, brushless
Current range, continuous	50 - 165 A
Open circuit voltage	50 V
Duty cycle	165 A - 35%, 140 A - 60%
Electrode diameter	2 - 4 mm
Insulating class	H
ENGINE	Gasoline, 2-stroke, air cooled
Type	MOSA
Output *	6.6 kW (9 HP)
Speed	6000 rpm
Displacement / Cylinders	125 cm ³ /1
Fuel system	gasoline/oil mixture (50 : 1)
Fuel consumption	530 g/kWh

* Maximum output (not overloadable) according to ISO 3046/1

GENERAL SPECIFICATIONS	
Tank capacity	3 l
Running time (at duty cycle 60%)	1.5 h
Protection	IP 23
Dimensions Lxwxh (mm)	570x300x410
Weight	28 kg
Noise level	101 LWA (76 dB(A) - 7 m)

Values shown are nominal values. For further information please contact the sales department.